




POWER PACK - AIR COOLED

PREMIUM - 1 PUMP - 2,300 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.
- Equipped with Smart Draft™, a temperature monitoring technology.



MMPP4301




5-15P



www.micromatic.com • 1 (866) 327-4159

1/3 HP COMPRESSOR

Job Number: _____ Location: _____

PART NO.	DESCRIPTION	SHIPPING WEIGHT
 MMPP4301	Air cooled power pack, 1 pump and motor, equipped with Smart Draft™	55 kg 120 lbs

OPERATING PERFORMANCE

COMPRESSOR	1/3 HP	REFRIGERANT	R513a*
BTU PER HOUR	2,300	CHARGE	0.34 kg (12 oz)
PLUG TYPE (NEMA #)	5-15P	REFRIGERANT RUNNING PRESSURE	18 (low) 140 (high)
CORD LENGTH	8'	BATH CAPACITY	43.5 litre (11.5 gallons)
VOLTAGE	115	PUMP TYPE	Rotary Vane
RUNNING	12.1A	PUSH IN CONNECTOR	12.7mm (1/2") O.D.

*Beginning January 2023: Charged with R513a refrigerant
 *Prior to January 2023: Charged with R134a refrigerant

Power pack equipped with SMART DRAFT™, a temperature monitoring technology.

DIMENSIONS

