




# POWER PACK - AIR COOLED

PREMIUM - 2 PUMP - 3,600 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.
- Equipped with Smart Draft™, a temperature monitoring technology.



**MMPP4302-PKG**



**L5-30P**



[www.micromatic.com](http://www.micromatic.com) • 1 (866) 327-4159

1/2 HP COMPRESSOR

Job Number: \_\_\_\_\_ Location: \_\_\_\_\_

# SPECIFICATIONS

PART NO.	DESCRIPTION	SHIPPING WEIGHT
<b>MMPP4302-PKG</b>	Air cooled power pack, 2 pump and motor, equipped with Smart Draft™	71 kg 157 lbs

## OPERATING PERFORMANCE

COMPRESSOR	1/2 HP
BTU PER HOUR	3,600
PLUG TYPE (NEMA #)	L5-30P
CORD LENGTH	8'
VOLTAGE	115
RUNNING	21A

REFRIGERANT	R513a*
CHARGE	0.45 kg (16 oz)
REFRIGERANT RUNNING PRESSURE	18 (low) 140 (high)
BATH CAPACITY	43.5 litre (11.5 gallons)
PUMP TYPE	Rotary Vane
PUSH IN CONNECTOR	12.7mm (1/2") O.D.

Beginning January 2023: Charged with R513a refrigerant  
 Prior to January 2023: Charged with R134a refrigerant

Power pack equipped with SMART DRAFT™, a temperature monitoring technology.

## DIMENSIONS

