T-Guard+

Information

Description	Soft & Flexible Clear PVC Tubing manufactured using a phthalate free plasticiser.
Main Application	For use in the dispensing of beverages.
Certifications	NSF-51

Materials

Mono Layer	-	100% Virgin Soft Clear PVC

Tubing Properties

	Inner ø	Outer ø	Safe Working Pressure (bar)	**Pressure Loss (mbar) 2.1 l/min	5.0 l/min
Imperial	0.187"	0.438"	12.7	128	-
	0.250"	0.500"	10.6	-	147
	0.312"	0.563"	9.0	-	50
	0.375"	0.625"	7.0	-	22
	0.500"	0.750"	6.0	-	6

Maximum Operating Temperature	35 °C
Minimum Roughness	N/A

Notes / Copyright

*Any figures for gas permeation are given in units of $cm^3/m/day/bar$. **Pressure loss properties were determined by assuming a flow of water at 20°C through 1 metre of tubing with a fluid flow rate of 2.1 / 5.0 litres per minute.

© Valpar Micro Matic Limited
Valpar Micro Matic Ltd proprietary and confidential information. All design rights or other intellectual property rights in this document and the copyright in this document are the property of Valpar Micro Matic Limited. Any unauthorised use thereof will constitute an infringement of the intellectual property rights of Valpar Micro Matic Limited.

DOCUMENT ISSUE NUMBER : 1